

Fitlet2

Compact IoT gateway with Intel® Atom® processor



- Intel® Apollo Lake E3900 Atom processor
- Up to 4 x Gigabit Ethernet ports
- SATA M.2 or 2.5" storage device
- Up to 8 x USB 3.0 / 2.0 ports
- Optional Wi-Fi/BT + LTE modem
- RS-232 serial port
- Up to 9V-36V DC power input
- Side/bottom VESA / DIN Rail mounting
- Rugged, MIL-STD-810G
- 112 x 84 x 34mm
- 5-year warranty

Category	Specification	Details
CPU	Intel Atom x7-E3950	4 cores • 1.6 / 2.0 GHz • 2 MB cache • 12 W
	Intel Celeron J3455	4 cores • 1.5 GHz • 2 MB cache • 10 W
	Intel Atom x5-E3930	2 cores • 1.3 / 1.8 GHz • 2 MB cache • 6.5 W
Memory	DDR3 SO-DIMM	Up to 16 GB • Up to 1866 MT/s
Display	HDMI 1.4	3840x2160 @ 30 Hz
	mini-DP 1.2	4096x2160 @ 60 Hz • Dual-mode • Daisy-chain (3rd display)
Storage	SATA	Standard SATA device
	M.2 Key-M	On-board up to 2260 • Optional up to 2280 (FACET)
	Optional 2.5" SATA	SSD/HDD (requires deep bottom cover)
Networking – LAN	On-board	2 x 1 GbE (RJ45)
	Optional modules	FC-M2LAN: 2 x 1 GbE • FC-POED: 1 x 1 GbE + PoE • FC-OPLN: 2 x 1 GbE (SFP+)
Wireless & Cellular	Wi-Fi / BT	Wi-Fi 5 • BT 4.2 • M.2 Key-E
	Cellular options	FC-CEM: M.2 Key-B (LTE/4G) • FC-PCI: miniPCIe (LTE/4G)
USB	Ports	2 x USB 3.0 Type-A • 2 x USB 2.0 Type-A
Audio	Digital / Analog	HDMI & DP audio • 3.5 mm input + output
Serial / GPIO / CAN	On-board	RS-232 (mini-serial)
	Optional	FC-SCG: RS-232/485 + CAN + GPIOs
TPM	Security	Intel PTT (on-board) • Optional TPM 2.0 module
FACET Modules	Expansion options	FC-M2LAN • FC-POED • FC-OPLN • FC-CEM • FC-PCI • FC-SCG • FC-USB (4 x USB 2.0 + M.2 Key-E + Key-M 2280)