

Fitlet3

Fanless Atom mini-PC for industrial and IoT applications



- IoT gateway / Fanless industrial PC
- Intel® Elkhart Lake x6000E Atom processor
- MIL-STD-810G
- 2 × or 4 × 1 or 2.5 Gigabit LAN
- Optional Wi-Fi/BT + LTE/5G modem
- Optional AI accelerator
- Optional Isolated serial + GPIO ports
- 9V – 42V DC power input

Category	Specification	Details	
CPU	Intel Atom x6425E	4 cores • 2.0 / 3.0 GHz • 12 W	
	Intel Celeron J6413	4 cores • 1.8 / 3.0 GHz • 10 W	
	Intel Atom x6211E	2 cores • 1.3 / 3.0 GHz • 6 W	
Memory	DDR4 SO-DIMM	Up to 32 GB • Up to 3200 MT/s	
Storage	M.2 Key-M	PCIe x4 / SATA • NVMe or M.2 SATA • up to 2280	
	M.2 Key-B	SATA up to 2260 • shared with LTE/5G modem	
	2.5" SATA	Optional via M.2-to-SATA expansion (EB-M2SATA)	
AI Accelerator	Hailo-8 options	M.2 Key-M PCIe x4 (26 TOPS) • M.2 Key-A+E PCIe x1 (26 TOPS)	
Display	HDMI 1.4b	3840×2160 @ 30 Hz	
	mini-DP 1.2	4096×2160 @ 60 Hz • Dual-mode	
Ethernet	On-board	2 × 1 GbE (RJ45)	
	Optional modules	FC3-LAN2G5: 2 × 2.5 GbE • FC3-LAN: 2 × 1 GbE • FC3-OPLN: 1 × SFP+ • FC3-POED: 1 × GbE + PoE	
Wireless & Cellular	On-board	Optional Wi-Fi 6E + BT 5.2	
	M.2 Key-E	Wi-Fi 6E / BT 5.2 module or AI accelerator	
	M.2 Key-B	LTE/5G modem + micro-SIM tray (mutual with M.2 SATA)	
USB	USB 2.0	4 × USB 2.0 Type-A	
	USB 3.1	2 × USB 3.1 Type-A	
Serial / GPIO	Optional	Isolated RS-232/422/485 + 2× GPI + 2× GPO (terminal block)	
Audio	Optional	I2S codec • Analog in/out on 3.5 mm jacks	
	Power	Input	9–42 V DC • up to 3.33 A
	Connector	5.5 mm locking power jack	
	Optional	FC3-POE: PoE input + GbE	
TPM	Security	Intel PTT (TPM 2.0) • Optional discrete TPM 2.0	
OS Support	Windows	Windows 10 IoT LTSC 2021 • Windows 10 Pro • Windows 11 Pro	
	Linux	Linux Mint • Ubuntu	

Operating Environment	Temperature	0–45°C (commercial) • -20–70°C (extended) • -40–85°C (industrial)
	Humidity	5–95% non-condensing
Physical	Cooling	Fanless passive
	Dimensions	132.8 × 100 × 34.8 mm
	Weight	~420 g
	Mounting	VESA • DIN rail (side or bottom)
Front Panel I/O	Ports	2 × USB 2.0 • HDMI 1.4b • mini-DP 1.2 • Power jack • Optional terminal block • 2 × RJ45
Rear Panel I/O	Ports	Power button • 2 × USB 3.1 • Optional 3.5 mm audio • Micro-SIM tray • Debug LED • 2 × USB 2.0
Side Panels	Antennas	Optional 2 × SMA (Wi-Fi/BT or cellular) on each side
	FACET	Optional FACET connectors (Ethernet, serial, etc.)
Internal Slots	SO-DIMM	DDR4 module
	M.2 Key-M	NVMe/SATA storage • AI module • or 2.5" SATA expansion
	M.2 Key-B	LTE/5G modem • SATA storage • or 2.5" SATA expansion
	M.2 Key-E	Wi-Fi/BT module or FACET card
FACET Modules	Expansion options	FC3-LAN2G5 • FC3-LAN • FC3-POED • FC3-OPLN • FC3-SC-S2 • FC3-SC-C2 • FC3-SC-S1C1 • EB-M2SATA
Accessories	Optional	PSU • VESA bracket • DIN rail kits • Remote power button