

# LIVA M600

Compact fanless PC with wide-range power



Category	Specification
<b>Platform</b>	Intel® Alder Lake-N, TDP 15W <ul style="list-style-type: none"> <li>• Intel® Core™ i3-N305, 6M Cache, up to 3.80 GHz</li> <li>• Intel® Processor N200, 6M Cache, up to 3.70 GHz</li> <li>• Intel Atom® x7211E, 6M Cache, up to 3.20 GHz</li> <li>• Intel Atom® x7425E, 6M Cache, up to 3.40 GHz</li> </ul>
<b>Expansion Slots</b>	<ul style="list-style-type: none"> <li>• 1 × M.2 2280 Key-M (PCIe Gen3x1, SATA)</li> <li>• 1 × M.2 2230 Key-E (WLAN)</li> <li>• 1 × M.2 Key-B (3042/3052, WWAN) + nano-SIM slot</li> <li>• 1 × RS232/422/485</li> <li>• 3 × RS232 (Front Panel)</li> </ul>
<b>Memory</b>	1 × SO-DIMM DDR5 4800 MHz, up to 16 GB
<b>Storage</b>	1 × M.2 2280 SATA3 / PCIe Gen3 x1 NVMe SSD
<b>Audio</b>	HDMI™ Audio
<b>Networking</b>	2 × 2.5 GbE LAN (Intel® I226-V)
<b>USB</b>	<ul style="list-style-type: none"> <li>• 4 × USB 3.2 Gen 2x1 (Rear)</li> <li>• 2 × USB 2.0 (Front)</li> </ul>
<b>Video Output</b>	2 × HDMI™ ports
<b>Wireless</b>	1 × WLAN (Intel® AX211, up to 3 Gbps)
<b>Power</b>	1 × Screw-type DC-in (9–36 V wide-range)
<b>VESA Mount</b>	100 × 100 mm (optional)
<b>Dimensions</b>	200 × 125 × 39.5 mm
<b>OS Support</b>	Windows® 11 Linux
<b>Accessories</b>	90 W adapter, wall mount, quick guide, antenna
<b>Remarks</b>	<ul style="list-style-type: none"> <li>• Supports VESA mount &amp; DIN rail (optional)</li> <li>• Kensington lock</li> <li>• Fanless thermal design</li> </ul>
<b>Operating Conditions</b>	<ul style="list-style-type: none"> <li>• Operating temp: -5 °C to 50 °C (with wide-temp M.2 SSD, memory, 0.7 m/s airflow)</li> <li>• Storage temp: -20 °C to 60 °C</li> <li>• Storage humidity: 5%–90% (non-condensing)</li> </ul>