

# Tensor-i20



## Common Specifications (shared by all four models)

Category	Shared Specification
<b>CPU &amp; Performance</b>	ARM or x86 industrial-grade processor, hardware watchdog, low-power design
<b>Memory &amp; Storage</b>	2–8 GB RAM, 8–64 GB eMMC, microSD expansion
<b>Operating System</b>	Linux-based OS, container support (Docker/OCI), OTA updates
<b>Networking Protocols</b>	IPv4/IPv6, DHCP, DNS, VLAN 802.1Q, static routing, firewall, VPN (IPsec/OpenVPN/WireGuard)
<b>Security</b>	Secure boot, TPM/crypto chip, TLS 1.2/1.3, role-based access control
<b>Industrial Features</b>	Wide temperature range (-20°C to +70°C), DIN-rail mount, surge protection
<b>Power Input</b>	12–48 VDC wide-range input
<b>Management</b>	Web UI, REST API, SNMP, remote fleet management
<b>Certifications</b>	CE, FCC, RoHS, industrial EMC compliance

## Differences Between the Four Models

Feature Category	Multi-LAN Model	Multi-COM Model	Multi-PoE Model	Multi-IoT Model
<b>Primary Function</b>	High-density Ethernet routing/switching	Serial communication gateway	Power-over-Ethernet networking	IoT protocol aggregation
<b>LAN Ports</b>	4–8× Gigabit LAN/SFP	2× LAN	4× PoE/PoE+ ports	2× LAN
<b>PoE Support</b>	No	No	Yes (IEEE 802.3af/at)	Optional
<b>Serial Ports</b>	Optional (1–2)	4–8× RS-232/485	Optional (1)	2× RS-485
<b>IoT Protocols</b>	Basic MQTT	Modbus RTU/TCP	Basic MQTT	Full IoT stack: MQTT, OPC-UA, LoRaWAN, Zigbee, BLE
<b>Wireless Options</b>	Optional Wi-Fi/LTE	Optional LTE	Optional Wi-Fi	Wi-Fi, LTE/5G, BLE, optional LoRa
<b>Power Budget</b>	Standard	Standard	High PoE budget (60–120 W)	Standard
<b>Use Case</b>	Network segmentation, industrial LAN	Serial device integration	IP cameras, sensors, PoE devices	Multi-protocol IoT gateway